

EMPLEX

BAG SEALING SOLUTIONS

MPS 6100 Series Continuous Band Sealer

The MPS 6000 series of sealers offer you the highest quality and utmost reliability of any machine on the market at the most effective price. Key design features include; a unique Teflon band tensioner, tool-less access to the seal section, removable sealing sections, the ability to easily add options to the machine in the field, customizable stands, and much more.

The MPS 6100 models are stand alone bag sealers capable of sealing bags up to 2 pounds in weight (on an 8" wide bag, 2 mil bag) without the use of a conveyor. These sealers can seal bags up to 6 mil in thickness at production rates.

Designed for 24/7 operation, these sealers are suitable for all production environments.



TECHNICAL SPECIFICATIONS

Electrical:	120 volts, 6 amps.
Infeed Direction:	Right to Left.
Motor:	Variable Speed DC drive
Seal Throat Depth:	70 mm / 2.75"
Sealing Section:	125 mm / 5" of heating. 125 mm / 5" of cooling.
Variable Speed:	Up to 12.7 m / 500" per minute.
Sealing Width:	6 mm / 1/4" standard.
Sealer Operation:	Vertical or Horizontal
Temperature Range:	0-230 degrees Celsius. 0-445 degrees Fahrenheit.
Temperature Controller:	Digital PID autotune controller.

Model	Configuration
MPS 6100	Standard Sealer
MPS 6110	Standard Sealer with Front End Trimmer
MPS 6120	Standard Sealer with Emboss Coder
MPS 6130	Standard Sealer with Dry Ink Printer
MPS 6140	Table Top Sealer (see 6140 brochure)
MPS 6150	Standard Sealer with Front End Trimmer & Dry Ink Printer
MPS 6160	Standard Sealer with Front End Trimmer & Emboss Coder

Telephone: 416-291-8085
Toll Free: 800-265-1775
Fax: 416-298-4328
Email: info@plexpack.com
www.plexpack.com



PLEXPACK

PLEXPACK Machinery Distributed By: