

EMPLEX

BAG SEALING SOLUTIONS

MPS 7500 Series Continuous Band Sealer

The MPS 7500 series are conveyORIZED bag sealers capable of sealing bags of any weight. These sealers can seal bags up to 12 mil in thickness at production rates (6 mil maximum when gusseted). These sealers are also ideal for when the speed of an MPS 6000 series machines is not enough to meet your manufacturing needs. The MPS 7500 comes standard with a S.S. 6" w x 6' l, adjustable height, food grade belt conveyor. A 12" x 10' roller/belt conveyor is an option (pictured). Conveyors are required for bags with a weight greater than 2 pounds for vertical sealing. Designed for 24/7 operation, these sealers are suitable for all production environments.



- ◆ Dimensions: 69" tall x 82" wide x 33 deep/
- ◆ Sealing Section: 10" of heating with 2 separate PID autotune temperature controllers. 10" of cooling via overhead cooling fan.
- ◆ Variable Speed up to 750 inches per minute/
- ◆ Seal Range: 16" - 45" from ground.
- ◆ Sealing Width: 1/4 standard.
- ◆ Electrical: 120 volt, 11 amps.

<i>Model</i>	<i>Configuration</i>
MPS 7500	ConveyORIZED Sealer
MPS 7510	ConveyORIZED Sealer with Front End Trimmer
MPS 7520	ConveyORIZED Sealer with Emboss Coder
MPS 7530	ConveyORIZED Sealer with Dry Ink Printer
MPS 7550	ConveyORIZED Sealer with Front End Trimmer & Dry Ink Printer
MPS 7560	ConveyORIZED Sealer with Front End Trimmer & Emboss Coder

Telephone: 416-291-8085
Toll Free: 800-265-1775
Fax: 416-298-4328
Email: info@plexpack.com
www.plexpack.com

PLEXPACK



PLEXPACK Machinery Distributed By: